

. Do not scale from this drawing.

- ### Undertakers Drawings.

- with FFA/Cement:grout minimum ratio of 12:1.

- by the Architect.

- CHUMES.

- | | |
|--------|----------------------------|
| 0-300 | Time 1 (main 150, 100 min) |
| 0-1000 | Time 2 (main 150, 100 min) |

- | | | |
|---------|-----------------|------------------------|
| 12-4311 | (info mainline) | type 2 (min 225x100mm) |
|---------|-----------------|------------------------|

- UNIVERSITY MICROFILMS INTL.

- ## WORKS.

14. MQC indicates 3000 mini access chamber.

15. PPIC indicates 4750 Polypropylene Inspection Chamber.

- WITH BUILDING REGULATIONS

BE INVESTIGATED/SURVEYED

PRIVATE FOOTPATH/DRIVEWAYS

Permeable blocks/setts (to Architects details).

or BS-EN 12620.

200mm 4/40mm permeable coarse graded aggregate

¹ layer of geotextile with minimum 300mm laps.

10

Rev	Date	By	Checked	Remarks
-----	------	----	---------	---------

501

David Heywood

Drawing

ΕΠΙΧΕΙΡΗΣΙΑΚΟ ΠΡΟΓΡΑΜΜΑ

12/05/2014	206	MOB	FEB 2014
------------	-----	-----	----------

connecting digital

Denby Dale, Huddersfield HD8 8QJ

Tel. 01484 868257 email: mail@bvconsulting.co.uk

Road

Required

supplies

Algebra 1

retained

NOI FOR CONSTRUCTION.