DS75 Street Screen Portfolio

Amscreen is a leading provider of screen solutions in Europe offering seamless, scalable deployments & support via our full service approach & RDM®



Suitable for: Outdoor Bus Shelter |Outdoor Free Standing I Single (Poster Option) / Dual Screen

A Full Service Screen Solution

- RDM® - Remote Device Monitoring
- OptimEyes Audience Analytics
- Single & Double Sided Options
- Ease of Install & Maintenance

Screen Hardware Summary

High Impact
Weatherproof, high bright displays bringing content alive whatever the weather

Distribution & Scalability
European production and plug and play design gives speed and flexibility

Ease of Install & Maintenance
Bespoke modular designs and jigs offer fast, non-disruptive installs and maintenance

Security & Future Proofed
Secure system via encryption and authentication protocols plus ease of leveraging new tech.

Software Summary

Smart Tracking & Sensors
Smart brightness® and optional audience tracking using leading tracking platform, OptimEyes via Quividi

Host Integration & Remote Management
Integration with host systems such as Ayuda, Scala, Broadsign etc & RDM® provision

Service Summary

RDM® Remote Smart Management
Alerts and automated data collection via unique system architecture

RDM® Remote Smart Maintenance
Integrated asset management and trouble ticketing to facilitate remote fixes

For more information on Amscreen's solutions contact: :
E info@amscreen.co.uk | T +44(0)1204 664333 | amscreen.eu

Specification Subject to Change

AMScreen digital solutions

DS75 Street Screen Portfolio

DS75 Bus Shelter
Single/Dual Sided

High impact versatile sign integrating with existing structures



Single (digital) sided display with rear backlit poster option

Dual (digital) sided display variant

Bus Shelter integration

Audience analytic camera on digital sides

Height: 2,261mm
Width: 1,336mm
Depth: 305mm
Note: all dimensions +/- 7mm

Weight: 400 to 420Kg

DS75 FSU
Single/Dual Sided

Super sized sign for maximum high street visibility



Single (digital) sided display with rear backlit poster variant

Dual (digital) sided display variant

Free standing

Provision for mains consumer panel

Height: 2,850mm
Width: 1,336mm
Depth: 305mm
Note: all dimensions +/- 7mm

Weight: 500 to 520Kg

Screen Specifications

The Displays
- 2500 nit 75 inch LCD panel
- 1080 X 1920 pixels
- Direct sunlight visible
- 9:16
- 5000:1 contrast ratio
- 16.7m display colours
- LED auto-brightness
- Smart Brightness® backlight control

Connectivity
- 4G multi network
- RDM® Remote Smart Management option
- 3rd party monitoring system options

Enclosure
- 9.5mm laminated glass
- Double side screen option
- Backlit rear poster option
- Modular field serviceable

Conformance
- CE (RED, LVD, EMC)
- RoHS and WEEE

Environmental
- -20 to +40°C. IP55 rated.
- Smart Coldstart®
- Smart Environmentals®
- Smart Exchange®

RDM® – Smart Management & Maintenance

Communication
- Secure global 4G communication
- Immediacy of data exchanges / feeds

Smart Management
- Centralised configuration
- Centralised data collection
- Automated alerts

Smart Reporting
- Full data reporting
- Live and historic
- Client web dashboard
- SLA reporting on KPIs

Smart Monitoring
- Temperatures
- Humidity
- Fans
- Brightness
- Media player / router
- Power
- CMS / RDM® communication

Smart Maintenance ®
- Remote fixes
- Trouble ticketing
- On-site maintenance management
- Asset management
- Modular swap-outs

End-to-End Services
- Helpdesk
- Hosting
- SIM management
- Remote updates
- Consultancy

For more information on Amscreen's solutions contact:
E info@amscreen.co.uk | T +44(0)1204 664333 | amscreen.eu

Specification Subject to Change

AMScreen digital solutions