

ROOF CONSTRUCTION: - DARK GREY MARLEY MODERN CONE-TILES ONTO TANGULISED BATTENS ONTO WELL LAPPED BREATHABLE MINIWAPLEX ROOF FELT ONTO PRE-FORMED TRUSSED RAFTERS - HO WARTH TIMBER OR SIMILAR APPROVED TO CURRENT BRITISH STANDARDS, 100x50mm MINORAR BEADED WALL PLATES WELL STRAPPED DOWN AT 1.2m $\varnothing$.

GROUND FLOOR: - 125mm CO BREED, 1100 MESH (ANTI CR) MINI CONG. COVER, STEEL FLO. INCLUDE MOVEMENT JOINTS, 50mm FLOOR GRADE KINGS 1200 G.D.P.M. ONTO BEAM BEHINDS SUITABLE FOR SPA HANDSTRON TO 10000 RESISTANT FOR USE

LIVING TO RETAINING WALL: - 120 SELF-ADHESIVE BITUMEN TANKING WELL LAPPED & TAPED TO WALL DPM & DPM, 50mm KINGSPAN & 150mm SAND PROTECTION.

CHANGING ROOM FLOORS: - TILE FINISH Laid TO FALL TO INT. GULLIES ONTO 150mm CONC., 1100 MESH TO BASE (40mm CONC. COVER) ONTO 100mm FLOOR GRADE KINGS INSULATION ONTO WELL LAPPED & TAPED TOGETHER & TO WALL DPM, ONTO A MINI. 200mm WELL COMPACTED SAND BLINDED HARDSCAPE.

ALLOW TO UNDERPIN FOUNDATIONS TO EXISTING BUILDING - ESPECIALLY FOR TRACTOR STORE

Scale:
 0m 4m
 0m 8m
 0m 16m
 0m 100m
 Scale 1:50
 Scale 1:100
 Scale 1:200
 Scale 1:1250
 (When to scale of original plan, bar = 8cm)

© Copyright Kirklees Metropolitan Council

[illegible]

0m Scale 1:50 4m
0m Scale 1:100 8m
0m Scale 1:200 16m
0m Scale 1:1250 100m



[When to scale of original plan, bar = 8cm]

© Copyright Kirklees Metropolitan Council