

JNP Group		Page 1
Woodvale House Woodvale Road Brighthouse, HD6 4AB		
Date 08/08/2022 10:54	Designed by chris.yates	
File B24321-JNP-92-XX-CL-C-1...	Checked by	
Innovyze	Network 2017.1.2	

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - England and Wales

Return Period (years)	2	PIMP (%)	100
M5-60 (mm)	19.000	Add Flow / Climate Change (%)	0
Ratio R	0.350	Minimum Backdrop Height (m)	0.020
Maximum Rainfall (mm/hr)	75	Maximum Backdrop Height (m)	1.500
Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200
Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	1.00
Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500

Designed with Level Soffits

Network Design Table for Storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
1.000	32.203	0.129	249.6	0.019	4.00	0.0	0.600	o	900	Pipe/Conduit	
1.001	13.590	0.046	295.4	0.065	0.00	0.0	0.600	o	900	Pipe/Conduit	
1.002	13.071	0.132	99.0	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	
1.003	3.391	0.058	58.5	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.000	66.24	4.27	80.765	0.019	0.0	0.0	0.0	1.98	1258.7	3.4
1.001	65.53	4.40	80.636	0.084	0.0	0.0	0.0	1.82	1156.4	14.9
1.002	66.57	4.22	80.540	0.000	3.5	0.0	0.0	1.01	17.8	3.5
1.003	66.32	4.26	80.408	0.000	3.5	0.0	0.0	1.32	23.3	3.5

JNP Group	Page 2
Woodvale House Woodvale Road Brighthouse, HD6 4AB	
Date 08/08/2022 10:54 File B24321-JNP-92-XX-CL-C-1...	
Innovyze	
Network 2017.1.2	

Area Summary for Storm

Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
1.000	-	-	100	0.019	0.019	0.019
1.001	-	-	100	0.065	0.065	0.065
1.002	-	-	100	0.000	0.000	0.000
1.003	-	-	100	0.000	0.000	0.000
				Total	Total	Total
				0.084	0.084	0.084

Free Flowing Outfall Details for Storm

Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D, L (mm)	W (mm)
1.003		82.350	80.350	80.350	0	0

JNP Group	Page 3
Woodvale House Woodvale Road Brighthouse, HD6 4AB	
Date 08/08/2022 10:54 File B24321-JNP-92-XX-CL-C-1...	
Innovyze	
Designed by chris.yates Checked by	Network 2017.1.2

Online Controls for Storm

Hydro-Brake® Optimum Manhole: 10 FCC, DS/PN: 1.002, Volume (m³): 13.4

Unit Reference	MD-SHE-0089-3500-1000-3500
Design Head (m)	1.000
Design Flow (l/s)	3.5
Flush-Flo™	Calculated
Objective	Minimise upstream storage
Application	Surface
Sump Available	Yes
Diameter (mm)	89
Invert Level (m)	80.540
Minimum Outlet Pipe Diameter (mm)	150
Suggested Manhole Diameter (mm)	1200

Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.000	3.5
Flush-Flo™	0.300	3.5
Kick-Flo®	0.632	2.8
Mean Flow over Head Range	-	3.1

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	2.7	1.200	3.8	3.000	5.8	7.000	8.7
0.200	3.4	1.400	4.1	3.500	6.2	7.500	9.0
0.300	3.5	1.600	4.3	4.000	6.7	8.000	9.2
0.400	3.4	1.800	4.6	4.500	7.0	8.500	9.5
0.500	3.3	2.000	4.8	5.000	7.4	9.000	9.8
0.600	3.0	2.200	5.0	5.500	7.7	9.500	10.0
0.800	3.1	2.400	5.2	6.000	8.1		
1.000	3.5	2.600	5.4	6.500	8.4		

JNP Group		Page 4
Woodvale House Woodvale Road Brighouse, HD6 4AB		
Date 08/08/2022 10:54 File B24321-JNP-92-XX-CL-C-1...	Designed by chris.yates Checked by	
Innovyze	Network 2017.1.2	

2 year Return Period Summary of Critical Results by Maximum Level (Rank 1)
for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000
 Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 0.000
 Hot Start Level (mm) 0 Inlet Coefficient 0.800
 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000
 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 0
 Number of Online Controls 1 Number of Time/Area Diagrams 0
 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.350
 Region England and Wales Cv (Summer) 1.000
 M5-60 (mm) 19.000 Cv (Winter) 1.000

Margin for Flood Risk Warning (mm) 300.0
 Analysis Timestep 2.5 Second Increment (Extended)
 DTS Status OFF
 DVD Status ON
 Inertia Status ON

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 240, 360, 480, 960, 1440
 Return Period(s) (years) 2, 30, 100
 Climate Change (%) 0, 0, 30

	US/MH		Return	Climate	First (X)	First (Y)	First (Z)	Overflow	Water
PN	Name	Storm	Period	Change	Surcharge	Flood	Overflow	Act.	Level
									(m)
1.000	08	30 Summer	2	+0%					80.882
1.001	09	30 Summer	2	+0%					80.882
1.002	10 FCC	30 Summer	2	+0%	2/15 Summer				80.881
1.003	12	15 Summer	2	+0%					80.457

	US/MH	Surcharged	Flooded		Pipe		Level
PN	Name	Depth	Volume	Flow / Overflow	Flow	Status	Exceeded
		(m)	(m ³)	Cap. (l/s)	(l/s)		
1.000	08	-0.783	0.000	0.00	3.4	OK	
1.001	09	-0.654	0.000	0.01	7.6	OK	
1.002	10 FCC	0.191	0.000	0.21	3.5	SURCHARGED	
1.003	12	-0.101	0.000	0.23	3.5	OK	

JNP Group		Page 5
Woodvale House Woodvale Road Brighthouse, HD6 4AB		
Date 08/08/2022 10:54 File B24321-JNP-92-XX-CL-C-1...	Designed by chris.yates Checked by	
Innovyze	Network 2017.1.2	

30 year Return Period Summary of Critical Results by Maximum Level (Rank 1)
for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000
 Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 0.000
 Hot Start Level (mm) 0 Inlet Coefficient 0.800
 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000
 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 0
 Number of Online Controls 1 Number of Time/Area Diagrams 0
 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.350
 Region England and Wales Cv (Summer) 1.000
 M5-60 (mm) 19.000 Cv (Winter) 1.000

Margin for Flood Risk Warning (mm) 300.0
 Analysis Timestep 2.5 Second Increment (Extended)
 DTS Status OFF
 DVD Status ON
 Inertia Status ON

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 240, 360, 480, 960, 1440
 Return Period(s) (years) 2, 30, 100
 Climate Change (%) 0, 0, 30

										Water
PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Level (m)	
1.000	08	60 Summer	30	+0%					81.098	
1.001	09	60 Summer	30	+0%					81.098	
1.002	10 FCC	60 Summer	30	+0%	2/15 Summer				81.098	
1.003	12	480 Summer	30	+0%					80.457	

		Surcharged		Flooded	Pipe		Level	
PN	US/MH Name	Depth (m)	Volume (m ³)	Flow / Cap.	Overflow (l/s)	Pipe Flow (l/s)	Status	Exceeded
1.000	08	-0.567	0.000	0.00		4.1	OK	
1.001	09	-0.438	0.000	0.01		9.7	OK	
1.002	10 FCC	0.408	0.000	0.21		3.5	SURCHARGED	
1.003	12	-0.101	0.000	0.23		3.5	OK	

JNP Group		Page 6
Woodvale House Woodvale Road Brighthouse, HD6 4AB		
Date 08/08/2022 10:54 File B24321-JNP-92-XX-CL-C-1...	Designed by chris.yates Checked by	
Innovyze	Network 2017.1.2	

100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000
 Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 0.000
 Hot Start Level (mm) 0 Inlet Coefficient 0.800
 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000
 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 0
 Number of Online Controls 1 Number of Time/Area Diagrams 0
 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.350
 Region England and Wales Cv (Summer) 1.000
 M5-60 (mm) 19.000 Cv (Winter) 1.000

Margin for Flood Risk Warning (mm) 300.0
 Analysis Timestep 2.5 Second Increment (Extended)
 DTS Status OFF
 DVD Status ON
 Inertia Status ON

Profile(s) Summer and Winter
 Duration(s) (mins) 15, 30, 60, 120, 240, 360, 480, 960, 1440
 Return Period(s) (years) 2, 30, 100
 Climate Change (%) 0, 0, 30

								Water
PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surge	First (Y) Flood	First (Z) Overflow	Overflow Act. Level (m)
1.000	08	60 Winter	100	+30%				81.490
1.001	09	60 Winter	100	+30%				81.490
1.002	10 FCC	60 Winter	100	+30%	2/15 Summer			81.488
1.003	12	480 Winter	100	+30%				80.457

		Surcharged		Flooded	Pipe		Level	
PN	US/MH Name	Depth (m)	Volume (m³)	Flow / Cap.	Overflow (l/s)	Pipe Flow (l/s)	Status	Exceeded
1.000	08	-0.175	0.000	0.01		5.0	OK	
1.001	09	-0.046	0.000	0.02		10.5	OK	
1.002	10 FCC	0.798	0.000	0.21		3.5	SURCHARGED	
1.003	12	-0.101	0.000	0.23		3.5	OK	