


Technical Specification

	Original Setting		Minimum Setting		Maximum Setting	
Control Point	Head (m)	Flow (l/s)	Head (m)	Flow (l/s)	Head (m)	Flow (l/s)
Primary Design	2.100	3.500	2.100	3.148	2.100	3.800
Flush-Flo™	0.332	2.575	0.413	2.120	0.305	2.955
Kick-Flo®	0.674	2.079	0.673	1.862	0.674	2.268
Mean Flow		2.656		2.338		2.923



hydro-int.com/patents



Head (m)	Flow (l/s)
0.000	0.000
0.072	1.549
0.145	2.306
0.217	2.498
0.290	2.567
0.362	2.572
0.434	2.542
0.507	2.481
0.579	2.370
0.652	2.168
0.724	2.148
0.797	2.243
0.869	2.333
0.941	2.420
1.014	2.503
1.086	2.583
1.159	2.660
1.231	2.735
1.303	2.808
1.376	2.879
1.448	2.947
1.521	3.014
1.593	3.079
1.666	3.143
1.738	3.205
1.810	3.266
1.883	3.326
1.955	3.384
2.028	3.442
2.100	3.498

DESIGN ADVICE

The head/flow characteristics of this SHE-0075-3500-2100-3500 Hydro-Brake® Optimum Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve.



The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.



DATE	23/11/2024 12:52
Site	Yew Tree Road, Birchencliffe
DESIGNER	Michael Micklethwaite
Ref	22046-1

SHE-0075-3500-2100-3500
Hydro-Brake® Optimum