



- REMARKS:**
- * All measures in cm.
 - * Measures 20,70 m x 20,70 m, to be checked by diagonal measurement 29,27 m.
 - * Take care of accurate measurement, square and levelled.
 - * Lowest point of excavation always above maximum groundwaterlevel
 - * Dike slope is 1:1 (45 degrees)
 - * Concrete plate exact in middle.
 - * Recess pointing to loading location.
 - * Subsoil has to be free of sharp and edgy objects.
 - * Trench for pipe parallel to angle of inclination: width 50 cm., depth 50 cm. Installation of pipe in sand.
 - * Dikes to be covered by dikeslopeprotection.
 - * anchor trench must be at least 30 cm deep en wide.
 - * sand excavated from anchor trench is needed to fill the trench up after installation of dikeslope protection.

Alberts Alligator		FABRIEK DEER KUNSTSTOFBANK	
Wijk 37B, Postbus 44, 8700 AJ Wageningen, Tel. 0317 - 491944, Fax. 0317 - 429464		BOUWEN IN TEGEL	
Drawing groundwork Alligator bagbank		Capaciteit : 10000 m ³	
INDEX NO.		DAGUM 31-11-2008 2007	
TEK. NO.		SOORT 10000 m ³ 10000 m ³ 10000 m ³	
TEK.		TEK.	
FORSMANT		AI	