


## Technical Specification

Control Point	Head (m)	Flow (l/s)
Primary Design	2.100	3.500
Flush-Flo™	0.332	2.575
Kick-Flo®	0.674	2.079
Mean Flow		2.656

Hydro-Brake® Optimum Flow Control including:

- 3 mm grade 304L stainless steel
- Integral stainless steel pivoting by-pass door allowing clear line of sight through to outlet, c/w stainless steel operating rope
- Beed blasted finish to maximise corrosion resistance
- Stainless steel fixings
- Rubber gasket to seal outlet
- Variable flow rate post installation via adjustable inlet
- Indicative Weight: 15 kg



**IMPORTANT:** ○ LIMIT OF HYDRO INTERNATIONAL SUPPLY  
 THE DEVICE WILL BE HANDED TO SUIT SITE CONDITIONS  
 FOR SITE SPECIFIC DETAILS AND MINIMUM CHAMBER SIZE REFER TO HYDRO INTERNATIONAL  
 ALL CIVIL AND INSTALLATION WORK BY OTHERS  
 \* WHERE SUPPLIED  
 HYDRO-BRAKE® FLOW CONTROL & HYDRO-BRAKE® OPTIMUM FLOW CONTROL ARE REGISTERED TRADEMARKS FOR FLOW  
 CONTROLS DESIGNED AND MANUFACTURED EXCLUSIVELY BY HYDRO INTERNATIONAL

**THIS DESIGN LAYOUT IS FOR ILLUSTRATIVE PURPOSES ONLY. NOT TO SCALE.**

<b>DESIGN ADVICE</b> 	The head/flow characteristics of this SHE-0075-3500-2100-3500 Hydro-Brake® Optimum Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve. <b>The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.</b>			
	DATE	21/03/2025 13:02		SHE-0075-3500-2100-3500 Hydro-Brake® Optimum
	SITE	Birchenclyffe		
	DESIGNER	Shaun Tonge		
REF				