

NOTES

1. INDICATIVE LIGHT SPILL DIAGRAM.
2. NOT FOR CONSTRUCTION.
3. INITIAL LIGHT LEVELS SHOWN.
4. SPILL AT GROUND FLOOR LEVEL.
5. LIGHT SPILL DIAGRAM TO BE READ IN CONJUNCTION WITH LIGHTING DOCUMENTS:
   4718-DFL-ELG-XX-CA-EO-13001-S3
   4718-DFL-ELG-XX-RP-EO-13001-S3

NOT FOR CONSTRUCTION

KEY PROPOSED

SYMBOL	DESCRIPTION
A	Indicative DW Windsor Pharola DS bollard complete with backlight shield. Max output 785 lumens, CCT 2700K
B	Indicative wall downlight, Ligma Gino 2, max output 204 lumens,CCT 2700K, mounting no greater than 2m from ground level

ISOLUX LINES

RED:	10.0	LUX
PINK:	5.00	LUX
BLUE:	1.00	LUX
YELLOW:	0.50	LUX
GREEN:	0.20	LUX

INDICATIVE LIGHT SPILL DIAGRAM
MF = 1 SCALE:NTS

STATUS	REV	AMENDMENT DESCRIPTION	DATE	CAD	CHKD	APPD
S3	P01	First Issue	15.09.2026	NW	DS	DS

DESIGNERS

DFL-UK (Designs for Lighting Ltd)
17/18 City Business Centre
Winchester, Hampshire, SO23 7TA
Tel: 01962 855080
Email: info@dfl-uk.com

PROJECT

LOWER CHATTS FARM

DRAWING TITLE

LIGHT SPILL DIAGRAM
INDICATIVE ONLY

DESIGNED	CAD	CHECKED	APPROVED
NW	NW	DS	DS

ISSUE DATE	SHEET	SCALE	SHEET SIZE
SEPT 2026	1 of 1	NTS	A2

DRAWING NUMBER: 4718-DFL-ELG-XX-LD-EO-13001

JOB NUMBER	STATUS	REVISION
4718	S3	P01

DFL CAD FILE: C:\Users\NickWeatherstone\Designs for Lighting Ltd\DFL - Documents\Design\Projects\4718 Lower Chatts Farm\02-Drawings\4718-DFL-ELG-XX-LD-EO-13001-S3-P01.dwg